

Equipment tested by BAM for resistance to internal burnout by oxygen O2					
			<u> </u>		
Hydrogen pres	sure regulators&hydrogen equipment for industr	rial gases Pressure p1	Pressure p2	Flow Q	used for
Oxygen pressur	e regulator				
M59	Cylinder pressure regulator	200bar	up to 10bar	40m³/h	Hydrogen cylinders
Oxygen pressur	e regulator				
ZD60	Central pressure regulator	300bar	up to 30bar	60m³/h	ZD60 Gas supply stations
Oxygen pressur	e regulator				
ZD150	Central pressure regulator	300bar	up to 40bar	150m³/h	ZD150 Gas supply stations
Oxygen pressur	<u> </u>				
ZD400	Central pressure regulator	300bar	up to 20bar	400m³/h	ZD400 Gas supply stations
DV5	Double shut-off valve	300bar			ZD60 / ZD150 / ZD400 Gas supply stations
CD.	Manifold with the old value	200h a r			LID Manifeld CD with about value
SR	Manifold with check valve	300bar			HD Manifold SR with check valve
AV6	Shut-off valve	300bar			HD Manifold SR, ZD60 / ZD150 / ZD400 Gas supply stations
EV	Relief valve	300bar			HD Manifold SR
Hydrogen pres	urity gases up to 6.0		Flow Cv		
HP100	Cylinder pressure regulator	300bar	up to 17bar	Cv 0,06	Hydrogen cylinders
HP300	Line pressure regulator	300bar	up to 17bar	Cv 0,06	Pipeline constrution
HP230	Cylinder station HP 230	200bar	up to 17bar	Cv 0,06	1x1 Cylinders (bundle) single-stage with internal purge system
HP240	Cylinder station HP 240	200bar	up to 17bar	Cv 0,06	2x1 Cylinders (bundle) single-stage with manuel changeover
HP250	Cylinder station HP 250	200bar	up to 12bar	Cv 0,06	2x1 Cylinders (bundle) single-stage with automatic changeover